查询ZXMN6A07F供应商

ZXMN6A07F

60V N-CHANNEL ENHANCEMENT MODE MOSFET

SUMMARY
$V_{(BR)DSS}$=60V; $R_{DS(ON)}$=0.4Ω I_D=1A

DESCRIPTION

This new generation of TRENCH MOSFETs from Zetex utilises a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.



SOT23

FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- SOT23 package



APPLICATIONS

- DC - DC Converters
- Power Management Functions
- Relay and Solenoid driving
- Motor control

ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZXMN6A07FTA	7″	8mm	3000 units
ZXMN6A07FTC	13″	8mm	10000 units

DEVICE MARKING

- 7N6



Top View

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V_{DSS}	60	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current V_{GS}=10V; T_A=25°C(b) V_{GS}=10V; T_A=70°C(b) V_{GS}=10V; T_A=25°C(a)	I_D	1.0 0.84 0.93	A
Pulsed Drain Current (c)	I_{DM}	4	A
Continuous Source Current (Body Diode) (b)	I_S	1	A
Pulsed Source Current (Body Diode)(c)	I_{SM}	4	A
Power Dissipation at T_A=25°C (a) Linear Derating Factor	P_D	625 5	mW mW/°C
Power Dissipation at T_A=25°C (b) Linear Derating Factor	P_D	806 6.4	mW mW/°C
Operating and Storage Temperature Range	T_j:T_{stg}	-55 to +150	°C

THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient (a)	$R_{\theta JA}$	200	°C/W
Junction to Ambient (b)	$R_{\theta JA}$	155	°C/W

NOTES

(a) For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions

(b) For a device surface mounted on FR4 PCB measured at t≤5 secs.

(c) Repetitive rating 25mm x 25mm FR4 PC, D =0.05, pulse width 10μs - pulse width limited by maximum junction temperature. Refer to Transient Thermal Impedance graph.

CHARACTERISTICS



ELECTRICAL CHARACTERISTICS (at TA = 25°C unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	60			V	I_D=250μA, V_{GS}=0V
Zero Gate Voltage Drain Current	I_{DSS}			1	μA	V_{DS}=60V, V_{GS}=0V
Gate-Body Leakage	I_{GSS}			100	nA	V_{GS}=±20V, V_{DS}=0V
Gate-Source Threshold Voltage	$V_{GS(th)}$	1.0		3.0	V	I_D=250μA, V_{DS}= V_{GS}
Static Drain-Source On-State Resistance (1)	$R_{DS(on)}$		0.3	0.40 0.55	Ω Ω	V_{GS}=10V, I_D=1.8A V_{GS}=4.5V, I_D=1.3A
Forward Transconductance (3)	g_{fs}		2.3		S	V_{DS}=15V,I_D=1.8A
DYNAMIC (3)						
Input Capacitance	C_{iss}		166		pF	V_{DS}=40 V, V_{GS}=0V, f=1MHz
Output Capacitance	C_{oss}		19.5		pF	
Reverse Transfer Capacitance	C_{rss}		8.7		pF	
SWITCHING(2) (3)						
Turn-On Delay Time	$t_{d(on)}$		1.8		ns	V_{DD} =30V, I_D=1.8A R_G=6.0Ω, V_{GS}=10V
Rise Time	t_r		1.4		ns	
Turn-Off Delay Time	$t_{d(off)}$		4.9		ns	
Fall Time	t_f		2.0		ns	
Gate Charge	Q_g		1.65		nC	V_{DS}=30V, V_{GS}=5V, I_D=1.8A
Total Gate Charge	Q_g		3.2		nC	V_{DS}=30V,V_{GS}=10V, I_D=1.8A
Gate-Source Charge	Q_{gs}		0.67		nC	
Gate-Drain Charge	Q_{gd}		0.82		nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage (1)	V_{SD}		0.8	0.95	V	T_J=25°C, I_S=0.45A, V_{GS}=0V
Reverse Recovery Time (3)	t_{rr}		20.5		ns	T_J=25°C, I_F=1.8A, di/dt= 100A/μs
Reverse Recovery Charge (3)	Q_{rr}		21.3		nC	

NOTES

(1) Measured under pulsed conditions. Width≤300μs. Duty cycle ≤ 2% .

(2) Switching characteristics are independent of operating junction temperature.

(3) For design aid only, not subject to production testing.

TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS



Capacitance v Drain-Source Voltage



Gate-Source Voltage v Gate Charge



Basic Gate Charge Waveform



Gate Charge Test Circuit



Switching Time Waveforms



Switching Time Test Circuit

PACKAGE OUTLINE



PAD LAYOUT



SOT23 pattern.
Minimum Pad Size (dimensions in mm)

PACKAGE DIMENSIONS

DIM	MILLIMETRES		DIM	MILLIMETRES	
	MIN	MAX		MIN	MAX
A	2.67	3.05	H	0.33	0.51
B	1.20	1.40	K	0.01	0.10
C	—	1.10	L	2.10	2.50
D	0.37	0.53	M	0.45	0.64
F	0.085	0.15	N	0.95 NOM	
G	1.90 NOM		φ	10° TYP	

© Zetex plc 2002

Zetex plc
Fields New Road
Chadderton
Oldham, OL9 8NP
United Kingdom
Telephone (44) 161 622 4422
Fax: (44) 161 622 4420

Zetex GmbH
Streitfeldstraße 19
D-81673 München
Germany
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49

Zetex Inc
700 Veterans Memorial Hwy
Hauppauge, NY11788
USA
Telephone: (631) 360 2222
Fax: (631) 360 8222

Zetex (Asia) Ltd
3701-04 Metroplaza, Tower 1
Hing Fong Road
Kwai Fong
Hong Kong
Telephone: (852) 26100 611
Fax: (852) 24250 494

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to **www.zetex.com**

ISSUE 1 - MARCH 2002